



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449**

Specifications	TIMOR 1.0	TIMOR 1.3	TIMOR 1.6	TIMOR 1.9	TIMOR 2.5
CODE	TR100	TR101	TR102	TR103	TR104
Length [mm]	1020	1330	1630	1940	2560
Capacity [dm3]	620	830	1030	1204	1650
Cooling area of shelves [m2]	2	2,6	3,3	3,9	5,3
Depth [mm]	840	840	840	840	840
Height [mm]	2020+/-10	2020+/-10	2020+/-10	2020+/-10	2020+/-10
Unit weight [kg]	175	220	235	280	340
Refrigerant	R404a	R404a	R404a	R404a	R404a
	R507	R507	R507	R507	R507
	R448	R448	R448	R448	R448
	R449	R449	R449	R449	R449
Evaporating temperature [°C]	-10	-10	-10	-10	-10
Cooling power demand [W/mb]	1000	1000	1000	1000	1000
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	28,8	34	44,8	57,6	68
Rated power [W]	752,8	892	1180,8	1407,6	1812
Cooling power [W]	1111	1307	1755	1911	2425
Electricity consumption [kWh/24h]	10,5	12,5	16,5	19,7	25,4

Standard equipment

cooling system adapted to factor: R448A / R449A

dynamic cooling (ventilated)

insulated plastic sides with insulated glass - selectable colour (IGLOO colour chart)

ecological polyurethane foam insulation

base covering - powder painted steel - different colors available (Igloo pattern book)

front bottom panel made of coated steel - different colors available (Igloo pattern book)

top panel illuminated with LED light - different plexiglass colors available (IGLOO pattern book)

additional internal top illumination - LED lamp (color of choice: white, confectionery or meaty "deep pink")

interior and exposition shelves made of coated steel - different colors available (Igloo pattern book)

exposition shelves with height and angle adjustment

price stripes – different colors available (IGLOO pattern book)

bumper – different colors available (IGLOO pattern book)

night roller blind

automatic defrost

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

device prepared for multiplexing

device without side panels prepared for multiplexing (MOD/A)

external sectional night blind with lock (possible only with full side panels)

insulated plastic sides with insulated glass - selectable colour (IGLOO colour chart)

side panels made of double combined tempered glass or double combined mirror

insulated side panels made of white coated steel - thickness : 40 mm

customizable colour of side panels made of coated steel (contact the Igloo sales department)

insulated side panels made of stainless steel

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

custom front panel color (after consultation with the IGLOO Sales Department)

front panel color – different colors available (IGLOO pattern book)

base and front panel made of white coated steel (contact the Igloo sales department)

top full panel made of stainless steel

top wooden panel – different colors available (IGLOO pattern book)

wooden bumper – different colors available (IGLOO pattern book)

custom colors of device interior and exposition shelves

device interior and exposition shelves made of stainless steel

device interior and exposition shelves made of acid – resistant stainless steel

strengthening of full shelves

good securing fence

internal, upper lighting – LED lamp (color of choice: white, confectionery or meaty “deep pink”)

top mirrors

meat hooks – long

powder painted evaporator

automatic defrost

automatic condenser vaporization (electric evaporator)

fixed partition made of PETG (plexiglass)

electronic temperature recorder + software

recorder cable

