



Temperature range: **+2°C/+8°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290**

Specifications	PROXIMA SLIM OPEN 1.25	PROXIMA SLIM OPEN 1.88	PROXIMA SLIM OPEN 2.50	PROXIMA SLIM OPEN 3.75
CODE	PRXS100	PRXS101	PRXS102	PRXS103
Capacity [dm ³]	358	536	715	1073
The area of shelves [m ²]	2	3	4	6
Length [mm]	1250	1880	2500	3750
Depth [mm]	970	970	970	970
Height [mm]	1165+/-10	1165+/-10	1165+/-10	1165+/-10

Standard equipment

internal cooling aggregate

dynamic cooling (ventilated)

bottom shelf made of painted steel (Igloo pattern book)

exposition shelves on frame ,with height and angle adjustment, made of powder painted steel (Igloo pattern book)

external glass elements made of combined glass with argon filling and black, white or gray RAL7042 silkscreen

front panel with color-coated sheet - selectable color (IGLOO color guide)

base, coloured sheet - selectable colour (IGLOO colour chart)

price stripes - different colors available (IGLOO pattern book)

ecological polyurethane foam insulation

upper interior lighting + backlight of each shelf - different colors available (Igloo pattern book)

automatic defrost

automatic condenser vaporization

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

bottom shelf made of stainless steel

bottom shelf made of stainless steel

exposition shelves on frame ,with height and angle adjustment, made of stainless steel

exposition shelves on frame ,with height and angle adjustment, made of acid-resistant stainless steel

frame and internal back of device made of stainless steel

frame and internal back of device made of acid-resistant stainless steel

front panel color - different colors available (IGLOO pattern book)

base made of stainless steel

electronic temperature regulator with the registration system (Igloo)

recorder cable

no thermostat - 2 x temperature sensor NTC [10kΩ]

