



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a / R290**

Specifications	JOLA 700.1
CODE	JO100.1
Length [mm]	820
Capacity [dm <sup>3</sup> ]	700
Working capacity of the chamber [dm <sup>3</sup> ]	700
The area of shelves [m <sup>2</sup> ]	2,2
Exhibition area [m <sup>2</sup> ]	1,03
Polyurethane foam insulation thickness [mm]	40
Depth [mm]	740
Height [mm]	2000+/-10
Unit weight [kg]	120
Shelves dimensions [mm]	510x710
Maximum load [kg/m]	30
Refrigerant	R134a R290
Evaporating temperature [°C]	-15
Rated voltage [V]	230/50Hz
Rated power of lighting [W]	25,5
Rated power [W]	414
Cooling power [W]	549
Electricity consumption [kWh/24h]	5

## Standard equipment

internal cooling aggregate placed on the bottom

dynamic cooling (ventilated)

external housing made of coated steel - different colors available (Igloo pattern book)

interior made of white coated steel

hinged doors with combined glass – choice of door opening direction

ecological polyurethane foam insulation

5 pcs of plastified reticulated shelves, with height adjustment + lower base shelf

price stripes – different colors available (IGLOO pattern book)

top panel illuminated with LED light – different plexiglass colors available (IGLOO pattern book)

automatic defrost

condenser outlet to container

single vertical interior lighting – LED light

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

## Options

external housing color – different colors available (IGLOO pattern book)

external housing made of stainless steel

interior made of stainless steel

horizontally divided doors

hinged doors self – closer

door lock with key

fan stopping switch

plastified strengthened shelves

chrome reticulated shelves

chrome strengthened reticulated shelves

additional plastified reticulated shelf + handle set

additional plastified reticulated strengthened shelf + handle set

additional chrome reticulated shelf + handle set

additional chrome reticulated strengthened shelf + handle set

internal top and side illumination – LED lights

internal frame with 9 stainless steel drawers (excludes the interior lighting)

automatic condenser vaporization

device with temperature range from -6 °C to 0 °C

electronic temperature recorder + software

temperature recorder wire

SMS alarm module + temperature recorder with emergency power supply

USB-MGSM TTL wire for SMS module programming

