



Temperature range: **-18°C/-10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R404A / R507**

Specifications	BASIA 2/1.4M	BASIA 2/1.7M	BASIA 2/2.1 M	BASIA 2/2.5 M
CODE	KI101W	KI102W	KI103W	KI104W
Length [mm]	1380	1680	2010	2540
Capacity [dm ³]	240	300	360	400
The area of shelves [m ²]	0,9	1,2	1,4	1,6
Side panel thickness [mm]	40	40	40	40
Depth [mm]	1165	1165	1165	1165
Height [mm]	1230+/10	1230+/10	1230+/10	1230+/10
Unit weight [kg]	200	220	250	270
Refrigerant	R404A / R507	R404A / R507	R404A / R507	R404A / R507
Evaporating temperature [°C]	-30	-30	-30	-30
Cooling power demand [W/m ³]	400	400	400	400
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	8,5	22,4	22,4	28,8
Rated power [W]	905	995	1316	1945
Cooling power [W]	744	796	1085	1488
Rated power of electric heaters [W]	210	210	270	332
Rated power of the evaporator heater [W]	120	120	150	186
Electricity consumption [kWh/24h]	12,7	13,9	18,4	27,2
Load per shelf [kg/m]	30	30	30	30

Standard equipment

internal freezing aggregate

dynamic cooling (ventilated)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

display space with coloured sheet - selectable colour (IGLOO colour chart)

worktop - stainless steel

silver or gold aluminium profiles (IGLOO colour chart)

curved front glass openable

night blinds made of plexi glass

LED lamp (color of choice: white, confectionery or meaty "deep pink")

bumper - different colors available (IGLOO pattern book)

plastified reticulated baskets (765 x 295 mm)

double insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

automatic defrost

automatic condenser vaporization

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

siphoned condensate drain - diameter of the connector pipe Ø 40

refrigerant system adapted for one of the following media - R448a / R449a / R450a / R407F / R404A/R507 / R290

Options

device without side panels prepared for multiplexing (MOD/A)

housing with base panel from staff side made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color - different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

exposition area made of stainless steel

exposition area made of acid resistant stainless steel

powder painted evaporator

worktop - granite grey (thickness : 20 mm)

worktop - granite Balmoral (thickness : 20 mm)

worktop - granite black (thickness : 20 mm)

set of wheels (castors)

additional LED light in top lamp profile

electronic temperature recorder + software

recorder cable

customer front shelf (aluminum profile anodised color silver or gold)

runner for small movable table

small movable table for scale or cash register (400x500mm)

BASIA M

