



Temperature range: **+5°C/+15°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a / R290**

Specifications	KAMELEO 0.6 W	KAMELEO 0.9 W	KAMELEO 1.3 W
CODE	JA103K	JA102K	JA101K
Length [mm]	705	1005	1405
Length with the sides [mm]	705	1005	1405
Capacity [dm ³]	334	496	715
Working capacity of the chamber [dm ³]	334	496	715
The area of shelves [m ²]	1,2	1,8	2,6
Side panel thickness [mm]	38	38	38
Depth [mm]	960 +/-5	960 +/-5	960 +/-5
Height [mm]	1360 +/-10	1360 +/-10	1360 +/-10
Unit weight [kg]	120	170	220
Shelves dimensions [mm]	570x425 1szt, 570x515 1szt, 570x595 1szt, 290x525 2szt	870x425 1szt, 870x515 1szt, 870x595 1szt, 440x525 2szt	1280x425 1szt, 1280x515 1szt, 1280x595 1szt, 640x525 2szt
Refrigerant	R134a R290	R134a R290	R134a R290
Evaporating temperature [°C]	-10	-10	-10
Cooling power demand [W/mb]	800	800	800
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	28,8	34	68
Rated power [W]	316	551	732
Cooling power [W]	461	727	1025
Rated power of the evaporator heater [W]	160	160	200
Electricity consumption [kWh/24h]	4,7	8	10,6

Standard equipment

agregat chłodniczy wewnętrzny zasilany ekologicznym czynnikiem R290

dynamic cooling (ventilated)

front panel and plinth, wooden base - colour selectable (IGLOO colour chart)

small and thin wooden side panels - different colors available (IGLOO pattern book)

glass side panels or combined glass divider for multiplexable devices

curved front glass openable

ecological polyurethane foam insulation

stelaż wewnętrzny malowany na kolor srebrny , złoty, lub czarny (wzornik IGLOO)

3 pcs of glass exposition shelves with height and angle adjustment placed on the frame

bottom shelf made of stainless steel

back sliding doors with combined glass (KAMELEO 0.6 - hinged doors with choice of door opening direction)

upper interior lighting + additional illumination of each shelf - LED lights (confectionery color)

automatic defrost

automatic condenser vaporization

electronic temperature controller with digital display

condenser impurity or fan operation failure alarm

Options

the device without the wooden sides adapted for serial connection (mod/A)

the device without the wooden sides adapted for serial connection (mod/A)

additional front panel - different colors available (IGLOO pattern book)

additional side panels - different colors available (IGLOO pattern book)

additional thin side panels - different colors available (IGLOO pattern book)

internal frame made of stainless steel for 0.6 model

internal frame made of stainless steel for 0.9 model

internal frame made of stainless steel for 1.3 model

humidity control system

electronic temperature recorder + software

temperature recorder wire

small tray (400mm x 420mm)

medium tray (400mm x 510mm)

big tray (400mm x 590mm)

bottom tray (400mm x 520mm)

tylne drzwi przesuwne z szyb zespolonych z lustrem weneckim (w KAMELEO 0.6 drzwi rozwierne z lustrem weneckim)

KAMELEO (W)

